

Roca thinner S

Description and application

Thinner for epoxy and polyurethane. This product is no typical thinner.

Article number and packaging

21090-9 5 liter can

Properties

Good diluting properties

Properties liquid product

Colour	Transparent
Density	0,88 kg/l mixed product
Flash point	26 °C
Shelf life	At least 12 months after the date of production, if stored cool in unopened packaging and protected against frost. Products should always be placed on pallets to avoid direct contact with the floor.

Application and circumstances

Thinner only to be added once base(A) and harder(B) have been mixed.

Usage

Usage depends on the product, see label of product in question.

Important

Projects and applications can vary greatly. Always contact your supplier if you have doubts about a certain application, choice of material or surface treatment. Particularly with coating swimming pools and basins, special care is required throughout the entire process.

All the technical information given in this technical information sheet is based on laboratory tests. Information can change, depending on the conditions.

Legal notification

The information and, in particular, the recommendations concerning the application and final use of Prokol products is issued in good faith based on Prokol's current knowledge and experience of products that are correctly stored, handled and applied under normal conditions.

In practice, the differences in materials, surfaces and local conditions are such that no guarantee can be given concerning the marketability or suitability for a certain objective, nor can any liability arise from any legal relationship based on this information,

nor from any written recommendations or other advice that is given. The property rights of third parties must be respected.

Prokol guarantees that its products are free from manufacturing faults. Multi-component products are a finished product once the components have been mixed and processed. When mixed and processed correctly, the product will achieve the specifications given. Prokol can only guarantee the product when surfaces are processed and pre-treated correctly.

Users must always refer to the most recent product safety information sheet and product information sheet for the product concerned. Copies of the most recent editions are provided upon request and are available at www.prokol.com.

All our deliveries, acceptance of assignments, communications, advice, and agreements are subject to our general terms and conditions of delivery, filed with the Chamber of Commerce in Eindhoven under number 52327159. Any other terms and conditions are hereby expressly rejected.

The publication of this product information sheet makes all previous product information sheets for this product invalid.

* At 20 °C and 65% RH surface.
** At 1 kg and 20 °C product.



Tel. +31 (0)85 78 200 20
www.prokol.com • info@prokol.com

Liquid synthetic materials for a sustainable future